Internet Engineering Task Force
INTERNET-DRAFT

Vollbrecht et al.

April 23, 2003

State Machines for EAP Peer and Authenticator

Status of this Memo

This document is an Internet-Draft and is in full conformance with all provisions of Section 10 of RFC2026.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at http:// www.ietf.org/ietf/1id-abstracts.txt.

The list of Internet-Draft Shadow Directories can be accessed at http://www.ietf.org/shadow.html.

This Internet-Draft will expire on October 22, 2003.

Copyright Notice

Copyright (C) The Internet Society (2003). All Rights Reserved.

Abstract

This document describes a set of state machines for EAP Peer, EAP Authenticator (supporting local, passthrough and backend), for EAP Passthrough method, and for "backend adapter" that adapts EAP traffic carried by an AAA protocol such as RADIUS or Diameter to a Backend Authenticator. This set of state machines shows how EAP can be implemented to support deployment in either a Peer/AP or Peer/AP/AAA Server environmnet. The Peer and Authenticator machines are illustrative of how the EAP protocol defined in [I-D.ietf-eap-rfc2284bis] may be implemented. The Passtrhough method and "backend adapter" illustrate how EAP protocol support defined in [I-D.aboba-radius-rfc2869bis] may be implemented. Where there are differences [I-D.ietf-eap-rfc2284bis]/ [I-D.aboba-radius-rfc2869bis] are authoritative.

This document describes a state machine based on an EAP "Switch" model. This model includes events and actions for the interaction between the EAP Switch and EAP methods. The State Machine and associated model are informative only. Implementations may achieve the same results using different methods.

A brief description of the EAP "Switch" model is given in the Introduction section.

This document is still a work in progress. The authors believe it corresponds to the current state of revisions to the defining [I-D.ietf-eap-rfc2284bis]/[I-D.aboba-radius-rfc2869bis] documents, but it has not been vetted by the EAP working group as a whole. An appendix to this document points out issues the authors believe still need to be resolved between the documents. The intent is to synchronize this document with [I-D.ietf-eap-rfc2284bis] and [I-D.aboba-radius-rfc2869bis] revisions when they are released and then submit it as an RFC.

1 Specification of Requirements

In this document, several words are used to signify the requirements of the specification. These words are often capitalized. The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119].

2 The EAP Switch Model

This document offers a proposed state machine for RFCs [I-D.ietf-eap-rfc2284bis] and [I-D.aboba-radius-rfc2869bis] . There are state machines for the peer, the authenticator, a "passthrough method" and a "backend adapter". Accompanying each state machine diagram is a description of the variables, the functions and the States in the diagram. Whenever possible, the same notation has been used in both the peer and authenticator state machines.

An EAP authentication consists of one or more EAP methods in sequence followed by an EAP Success or EAP Failure sent from the Authenticator to the peer. The EAP Switches control negotiation of EAP methods and sequences of methods.



Figure 1: EAP Switch Model

At both the peer and authenticator one or more EAP method exists. The EAP switches select which

methods each is willing to use, and negotiate between themselves to pick a method or sequence of methods.

Note that the methods may also have state machines. The details of these are out of scope for this paper, with the exception of the Passthrough Method.



Figure 2: EAP Switch Model

The Passthrough Method appears to the Authenticator Switch as a method, but its function is to Pass EAP messages to a Backend Server where the real Authentication Method resides. This paper includes a state machine for a Passthrough method and a diagram the flow between an Authenticator with a Passthrough Method and the Backend and its Method.

This document describes a set of State Machines that can manage EAP authentication from the peerto an EAP method on the Authenticator or from the Peer through the Authenticator passthrough method to the EAP method on the Backend EAP server.

The state diagrams presented in this document have been coordinated with the IEEE 802.1X diagrams. The format of the diagrams is adapted from the 802.1X format. Portions of a version this document are included as Appendix F of 802.1X (2003).

3 Notational conventions used in state diagrams

3.1 Notational specifics

The following state diagrams have been completed based on the conventions specified in [IEEE.802-1X.2001], section 8.5.1. Much of that section is reprinted here for completeness.

State diagrams are used to represent the operation of a function as a group of connected, mutually exclusive states. Only one state of a function can be active at any given time. Each state is represented in the state diagram as a rectangular box, divided into two parts by a horizontal line. The upper part contains the state identifier, written in uppercase letters. The lower part contains any procedures that are executed on entry to the state.

All permissible transitions between states are represented by arrows, the arrowhead denoting the direction of the possible transition. Labels attached to arrows denote the condition(s) that must be

met in order for the transition to take place. A transition that is global in nature (i.e., a transition that occurs from any of the possible states if the condition attached to the arrow is met) is denoted by an open arrow; i.e., no specific state is identified as the origin of the transition.

On entry to a state, the procedures defined for the state (if any) are executed exactly once, in the order that they appear on the page. Each action is deemed to be atomic; i.e., execution of a procedure completes before the next sequential procedure starts to execute. No procedures execute outside of a state block. On completion of all of the procedures within a state, all exit conditions for the state (including all conditions associated with global transitions) are evaluated continuously until such a time as one of the conditions is met. All exit conditions are regarded as Boolean expressions that evaluate to True or False; if a condition evaluates to True, then the condition is met. When the condition associated with a global transition is met, it supersedes all other exit conditions, including UCT. The label UCT denotes an unconditional transition (i.e., UCT always evaluates to True). The label ELSE denotes a transition that occurs if none of the other conditions for transitions from the state are met (i.e., ELSE evaluates to True if all other possible exit conditions from the state evaluate to False).

A variable that is set to a particular value in a state block retains this value until a subsequent state block executes a procedure that modifies the value.

3.2 Document authority

Should a conflict exist between the interpretation of a state diagram and either the corresponding global transition tables or the textual description associated with the state machine, the state diagram takes precedence. When a discrepancy occurs between any part of this document (text or diagram) and any of the related documents ([I-D.ietf-eap-rfc2284bis], [I-D.aboba-radius-rfc2869bis], etc.) the latter (the other document) is considered authoritative and takes precedence.

4 Peer State Machine

The following is a diagram of the EAP Peer state machine. Also included is an explanation of the primitives and procedures referenced in the diagram, as well as a clarification of notation.



4.1 Interface between peer state machine and lower layer

The lower layer presents messages to the EAP peer state machine by storing the packet in eapReqData and setting the eapReq signal to TRUE. Note that despite the name of the signal, the lower layer does not actually inspect the contents of the EAP packet (it could be a Success or Failure message instead of a Request).

When the EAP peer state machine has finished processing the message it sets either eapResp or eapNoResp. If it sets eapResp, the corresponding response packet is stored in eapRespData. The

lower layer is responsible for actually transmitting this message. When the EAP peer state machine authentication is complete it will set eapSuccess or eapFailure to indicate to the lower layer that the authentication has succeeded or failed.

4.1.1 Variables (lower layer to peer)

- eapReq (boolean)

  set to TRUE in lower layer, FALSE in peer state machine. Indicates there is a request available in the lower layer.

- eapReqData (EAP packet)

  set in lower layer when eapReq is set to TRUE. The contents of the available request.

- portEnabled (boolean)

  Indicates that there is a valid port to use for the communication. If at any point the port is not available, portEnabled is set to FALSE and the state machine transitions to DISABLED (or BACKEND_DISABLED).

- aWhile (integer)

  outside timer used to indicate how long the peer has waited for a new (valid) request.

- altAccept (boolean)

  alternate indication of success, as described in [I-D.ietf-eap-rfc2284bis].

- altReject (boolean)

  alternate indication of failure, as described in [I-D.ietf-eap-rfc2284bis].

4.1.2 Variables (peer to lower layer)

- eapResp (boolean)

  Set to TRUE in peer state machine, FALSE in lower layer. Indicates there is a response to be sent.

- eapNoResp (boolean)

  Set to TRUE in peer state machine, FALSE in lower layer. Indicates the request has been processed, but there is no response to send.

- eapSuccess (boolean)

  Set to TRUE in peer state machine, FALSE in lower layer. Indicates the Peer has reached the SUCCESS state.

- eapFail (boolean)

  Set to TRUE in peer state machine, FALSE in lower layer. Indicates the Peer has reached the FAILURE state.

- eapRespData (EAP Packet)

  Set in peer state machine when eapResp is set to TRUE. The EAP packet which is the response to send.

- eapKey (EAP Key)

  Set in peer state machine when keying material becomes available. Set during the METHOD state. Note that this document does not yet define the structure of the type "EAP Key". We expect it to be defined in the EAP Keying Framework document.

4.1.3 Constants

- ClientTimeout (integer)

  Configurable amount of time to wait for a valid request before aborting.

- EapTunnelled (boolean)

  Indication of whether EAP is running inside a protected tunnel or not.

4.2 Interface between peer state machine and methods

IN: eapReqData, (reqId)

OUT: intCheck, eapRespData

IN/OUT: methodState, (method-specific state), (policy)

If methodState==INIT, the method starts by initializing its own method-specific state.

Next, the method must decide whether to process the packet or silently discard it. If the packet looks like it wasn't sent by the legitimate authenticator (e.g. it has invalid MIC, and this case should never occur), the method can set intCheck=FALSE. In this case, the method must not modify methodState, and it should not modify its own method-specific state.

If the method decides to process the packet, it behaves as follows.

- Updates its own method-specific state.
- Possibly tells Policy something.
- If the method has derived keying material it wants to export, stores the keying material to eapKey.
- Creates a response packet (with the same identifier as the request), and stores it to eapRespData.
- Sets intCheck=TRUE.

Finally the method must update methodState according to the following rules.

- NORMAL: The method is finished (either successfully or unsuccessfully), or at this point the server can decide that it doesn't want to continue with this method.

- CONTINUE: The method always continues at this point. That is, the method specification says that the server can't decide to end the method at this point.
- STRICT: Same as CONTINUE, but the method specification also forbids using Notifications at this point.
- CON_ACC: The server has signalled that the next packet will be EAP Success. Note that this is different from ordinary method success, and is probably relevant only for tunnelling methods (e.g. PEAP).
- CON_REJ: The server has signalled that the next packet will be EAP Failure. Note that this is different from ordinary method failure.

4.3 Peer state machine local variables

4.3.1 Long-term (maintained between packets)

- currentMethod (EAP Type)
  Set in GET_METHOD state. The method the peer believes to be currently "in progress"
- methodState (enumeration)
  As described above
- lastId (integer)
  Set in SEND_RESPONSE state. The EAP identifier value of the last request.
- lastRespData (EAP packet)
  Set in SEND_RESPONSE state. The EAP packet last sent from the peer.

NOTE: EAP type can be normal type (0..253,255), or an extended type consisting of type 254, Vendor-Id, and Vendor-Type.

4.3.2 Short-term (not maintained between packets)

- rxReq (boolean)
  Set in RECEIVED state. Indicates the current received packet is an EAP request.
- rxSuccess (boolean) Set in RECEIVED state. Indicates the current received packet is an EAP Success.
- rxFailure (boolean)
  Set in RECEIVED state. Indicates the current received packet is an EAP Failure.
- reqId (integer)
  Set in RECEIVED state. The identifier value associated with the current EAP request.
- reqMethod (EAP type)
  Set in RECEIVED state. The method type of the current EAP request
- intCheck (boolean)
  Set in METHOD state. Indicates whether the method has decided to accept the current packet.

4.4 Peer state machine procedures

- parseEapReq()

  Determine the code, identifier value, and type of the current request

- buildNotify()

  Create the appropriate notification response.

- resetCurrentMethod()

  Alert the current method that it has been aborted.

- Policy.allow()

  Determine if the Peer is allowed to perform a particular method at a particular point in the conversation.

- Policy.update()

  Update all variables related to internal policy state.

- Policy.isSatisfied()

  Determine if the policy will allow SUCCESS or not.

- m.integrityCheck()

  Method-specific procedure to test for the validity of a message.

- m.process()

  Method procedure to parse and process a request for that method.

- m.getKey()

  Method procedure to obtain key material for use by EAP or lower layers.

4.5 Peer state machine states

- DISABLED

  This state is reached anytime service from the lower layer is interrupted or unavailable. Immediate transition to INITIALIZE occurs when the port becomes enabled.

- INITIALIZE

  Initializes variables when the state machine is activated.

- IDLE

  The state machine spends most of its time here, waiting for something to happen.

- RECEIVED

  This state is entered when an EAP packet is received: the packet header is parsed here.

- GET_METHOD

  This state is entered when a request for a new type comes in: either the correct method is started, or a Nak response is built.

- METHOD

  The method processing happens here: the request from the authenticator is processed, and an appropriate response packet is built.

- SEND_RESPONSE

  This state signals the lower layer that a response packet is ready to be sent.

- DISCARD

  This state signals the lower layer that the request was discarded, and no response packet will be sent at this time.

- NOTIFICATION

  Handles requests for Notification method, and builds a response.

- RETRANSMIT

  Retransmits the previous response packet.

- SUCCESS

  A final state indicating success.

- FAILURE

  A final state indicating failure.

5 Authenticator State Machine

The following is a diagram of the EAP Authenticator state machine. Also included is an explanation of the primitives and procedures referenced in the diagram, as well as a clarification of notation.


(!portEnabled || eapBackendRestarting) && EapBackend
BACKEND_DISABLED
eapBackendRestarting = FALSE
portEnabled
BACKEND_INITIALIZE
if (eapRespData != NONE) {
(rxResp, respId, respMethod) = parseEapResp(eapRespData)
} else
rxResp = FALSE
if (rxResp)
currentId = respId
Policy.update(<...respMethod...>)
} else
currentId = NONE
rxResp && (respMethod==NAK || respMethod==EXPANDED_NAK)
else
(!portEnabled || eapRestarting) && !EapBackend
DISABLED
eapRestarting = FALSE
portEnabled
INITIALIZE
currentId = NONE
UCT
IDLE
aWhile = AuthenticatorTimeout
aWhile==0
eapResp
UCT
UCT
else
RETRANSMIT
retransCount++
if (retransCount <= MaxRetrans) {
eapReqData = lastReqData
eapReq = TRUE
}
RECEIVED
(rxResp,respId,respMethod)= parseEapResp(eapRespData)
DISCARD
eapResp = FALSE
eapNoReq = TRUE
SEND_REQUEST
retransCount = 0
lastReqData = eapReqData
eapResp = FALSE
eapReq = TRUE
else
!intCheck
else
retransCount > MaxRetrans
rxResp && (respId == currentId) && (respMethod == currentMethod || currentMethod == PASSTHROUGH)
METHOD
intCheck = (methodState != INIT) ? m.integrityCheck(eapRespData) : TRUE
if (intCheck) {
m.process(eapRespData)
Policy.update(<success|fail|other information>)
methodState = { PROPOSED | CONTINUE | END }
if (methodState != END) {
currentId = m.getNextId(currentId)
eapReqData = m.buildReq(currentId)
} else {
eapKey = NONE | m.getKey()
succFailData = NONE | m.buildSuccFail(currentId)
}
}
rxResp && (respId == currentId) && (currentMethod != PASSTHROUGH) && (respMethod==NAK || respMethod==EXPANDED_NAK) && (methodState == PROPOSED)
methodState == END
else
GET_METHOD
policySat = Policy.isSatisfied()
if (!policySat) {
currentMethod = Policy.getNextMethod()
methodState = { INIT | PICK_UP_INIT }
if (methodState == INIT)
eapRespData = NONE
}
NAK
Policy.update(<...>)
resetCurrentMethod()
UCT
!policySat && currentMethod == NONE
policySat
FAILURE
if (succFailData == NONE) {
currentId = nextId(currentId)
eapReqData = buildFailure(currentId)
} else {
eapReqData = succFailData
}
eapFail = TRUE
SUCCESS
if (succFailData == NONE) {
currentId = nextId(currentId)
eapReqData = buildSuccess(currentId)
} else {
eapReqData = succFailData
}
eapSuccess=TRUE

5.1 Interface between authenticator state machine and lower layer

The lower layer presents messages to the EAP authenticator state machine by storing the packet in eapRespData and setting the eapResp signal to TRUE.

When the EAP authenticator state machine has finished processing the message, it sets one of the signals eapReq, eapNoReq, eapSuccess, and eapFail. If it sets eapReq, eapSucess, or eapFail, the corresponding request (or success/failure) packet is stored in eapReqData. The lower layer is responsible for actually transmitting this message.

5.1.1 Variables (lower layer to authenticator)

- eapResp (boolean)

  Set to TRUE in lower layer, FALSE in authenticator state machine. Indicates an EAP response is available for processing.

- eapRespData (EAP packet)

  Set in lower layer when eapResp is set to TRUE. The EAP packet to be processed.

- portEnabled (boolean)

  Indicates that there is a valid port to use for the communication. If at any point the port is not available, portEnabled is set to FALSE and the state machine transitions to DISABLED.

- aWhile (integer)

  outside timer used to indicate how long the authenticator has waited for a new (valid) response.

- eapRestarting (boolean)

  Indicates the lower layer would like to restart authentication

- eapKey (EAP Key)

  Set in authenticator state machine when keying material becomes available. Set during the METHOD state. Note that this document does not yet define the structure of the type "EAP Key". We expect it to be defined in the EAP Keying Framework document.

5.1.2 Variables (authenticator to lower layer)

- eapReq (boolean)

  Set to TRUE in authenticator state machine, FALSE in lower layer. Indicates a new EAP request is ready to be sent.

- eapNoReq (boolean)

  Set to TRUE in authenticator state machine, FALSE in lower layer. Indicates the most recent response has been processed, but there is no new request to send.

- eapSuccess (boolean)

  Set to TRUE in authenticator state machine, FALSE in lower layer. Indicates the state machine has reached the SUCCESS state.

- eapFail (boolean)

  Set to TRUE in authenticator state machine, FALSE in lower layer. Indicates the state machine has reached the FAILURE state.

- eapReqData (EAP packet)

  Set in authenticator state machine when eapReq, eapSuccess, or eapFail is set to TRUE. The actual EAP request to be sent (or success/failure).

5.1.3 Constants

- AuthenticatorTimeout (integer)

  Configurable amount of time to wait for a valid response before aborting.

- MaxRetrans (integer)

  Configurable maximum for how many retransmissions should be attempted before aborting.

- EapBackend (boolean)

  Indication of whether the current state machine should be followed as if it is a backend server implementation.

5.2 Interface between authenticator state machine and methods

IN: eapRespData

IN/OUT: methodState, currentId, (method-specific state), (policy)

OUT: intCheck, eapReqData, succFailData

A. If methodState==PICK_UP_INIT: This signals that we should "pick up" a conversation that was started by someone else.

Some methods on a backend server may support this feature (usually only Identity, though others are possible). Policy knows what methods support this, and only those methods can end up in PICK_UP_INIT state.

The method behaves as follows.

- Initializes its own method-specific state, possibly using some information from Policy.
- Examines eapRespData, and updates its own method-specific state to match what it would have been if it had actually sent the corresponding request. (Obviously, this only works for methods that can determine what the initial request contained; Identity and EAP-TLS are good examples.)
- Moves to case C below.

This methodState is also used for the special PASSTHROUGH method, but it is documented elsewhere.

B. If methodState==INIT, we have not sent any requests yet. The method then sends its initial request as follows.

- Initializes its own method-specific state, possibly using some information from Policy (e.g. identity).
- Updates currentId to contain a new identifier value.
- Creates a new request packet (with the new identifier value), and stores it to eapReqData
- If the method is Identity or Notification, sets methodState=CONTINUE; in all other cases, sets methodState=PROPOSED.

C. Otherwise we have just received a response.

First the method must decide whether to process the packet or silently discard it. If the packet looks like it wasn't sent by the legitimate peer (e.g. it has invalid MIC, and this case should never occur), the method can set intCheck=FALSE. In this case, the method must not modify methodState or currentId, and it should not modify its own method-specific state.

If the packet is accepted, the options are to continue the conversation (send another request) or end the conversation. If the conversation is continued, the method behaves as follows.

- Updates its own method-specific state.
- Possibly tells Policy something.
- Updates currentId to contain a new identifier value.
- Creates a new request packet (with the new identifier value), and stores it to eapReqData.
- Sets methodState=CONTINUE and intCheck=TRUE.

If the method wants to end the conversation,

- Tells Policy about the outcome of the method, and possibly other information.
- If the method has derived keying material it wants to export, stores the keying material to eapKey.
- Sets succFailData=NONE (except special PASSTHROUGH method).
- Sets methodState=END.

5.3 Authenticator state machine local variables

5.3.1 Long-term (maintained between packets)

- currentMethod (EAP Type)
  EAP type, PASSTHROUGH, or NONE.
- currentId (integer)
  0-255 or NONE. Usually updated in METHOD state. Indicates the identifier value of the currently outstanding EAP request.
- methodState (enumeration)
  As described above.
- retransCount (integer)
  Set in SEND_REQUEST state. Current number of retransmissions.
- lastReqData (EAP packet)
  Set in SEND_REQUEST state. EAP packet containing the last sent request.

5.3.2 Short-term (not maintained between packets)

- rxResp (boolean)
  Set in RECEIVED state. Indicates the current received packet is an EAP response.
- respId (integer)
  Set in RECEIVED state. The identifier from the current EAP response.
- respMethod (EAP Type)
  Set in RECEIVED state. The method type of the current EAP response.
- succFailData (EAP packet)
  Set in METHOD state. Usage described above.
- intCheck (boolean)
  Set in METHOD state. Indicates whether the method has decided to accept the current packet.
- policySat (boolean)
  Set in GET_METHOD state. Stored value of last call to Policy.isSatisfied().

5.4 EAP authenticator procedures

- parseEapResp()
  Determine the code, identifier value, and type of the current response
- buildSuccess()
  Create an EAP Success Packet.

- buildFailure()

  Create an EAP Failure Packet.

- nextId()

  Determine the next identifier value to use, based on the previous one.

- resetCurrentMethod()

  Alert the current method that it has been aborted.

- Policy.update()

  Update all variables related to internal policy state.

- Policy.getNextMethod()

  Determine the method that should be used at this point in the conversation based on predefined policy.

- Policy.isSatisfied()

  Determine if the policy will allow SUCCESS or not.

- m.integrityCheck()

  Method-specific procedure to test for the validity of a message.

- m.process()

  Method procedure to parse and process a response for that method.

- m.buildSuccFail()

  Passthrough method to create a Success or Failure packet. More described above.

- m.buildReq()

  Method procedure to produce the next request.

- m.getNextId()

  Method procedure that is the parallel of the switch-level nextId(). Often it is up to the method to decide the next ID (particularly in backend authenticators).

- m.getKey()

  Method procedure to obtain key material for use by EAP or lower layers.

5.5 EAP authenticator states

- DISABLED

  The authenticator is disabled until the port is enabled by the lower layer.

- BACKEND_DISABLED

  Same for backend server.

- INITIALIZE

  Initializes variables when the state machine is activated.

- BACKEND_INITIALIZE
  Same for backend server. Also parses the headers of initial response packet (a response to a request sent by the NAS), if any.
- GET_METHOD
  This state chooses what should happen next: either a method is started, or the conversation is ended.
- IDLE
  The state machine spends most of its time here, waiting for something to happen.
- RECEIVED
  This state is entered when an EAP packet is received: the packet header is parsed here.
- METHOD
  This state builds request packets and processes responses received from the peer.
- SEND_REQUEST
  This state signals the lower layer that a request packet is ready to be sent.
- DISCARD
  This state signals the lower layer that the response was discarded, and no new request packet will be sent at this time.
- NAK
  This state processes Nak responses from the peer.
- RETRANSMIT
  Retransmits the previous request packet.
- SUCCESS
  A final state indicating success.
- FAILURE
  A final state indicating failure.

6 Passthrough and backend

6.1 Overview

There are two different cases to consider: either the first EAP request is sent by the NAS, or by the backend.

In the simple case, the NAS signals the backend that it wants to start an EAP conversation, and the backend sends the first EAP Request. This case could be handled with a very simple passthrough state machine.

The complex case is where the first EAP request (or several requests) are sent by the NAS, and at some point, the NAS switches to passthrough mode and backend takes over. This requires very careful handling to get right! After the backend has sent its first request, the situation is normal.

6.2 State machine overview

We could have drawn a separate passthrough authenticator and backend authenticator state diagrams, but this was not done because a) this way we can describe an authenticator that starts, b) the differences between the diagrams would have been rather small

The passthrough/backend split is specified using two copies of the authenticator state machine, one in the "passthrough" processor, and one in the "backend" processor.



The passthrough method takes EAP responses, encapsulates them into RADIUS Access-Request packets, and sends them to the backend. The passthrough method also translates the RADIUS response packet to appropriate EAP requests and signals to EAP authenticator switch.

The backend adapter state machine receives EAP responses from NAS inside RADIUS Access-Request packets, and passes these to the authenticator state machine using the normal lower layer interface. It also relays the signals returned by the authenticator state machine (e.g. eapReq, eapSuccess) to NAS using appropriate RADIUS messages.

6.3 Passthrough



If the first EAP request is sent by the backend, the NAS Policy simply activates the PASSTHROUGH method with methodState==INIT. The PASSTHROUGH method sends a RADIUS packet signalling EAP-Start to the backend, and relays messages.

In the case where the first EAP request is originated from the NAS, the NAS behaves as follows: Policy starts the (local) Identity method, which sends a request packet. When the response comes back, the Identity method processes it and sets methodState=END.

Policy then starts the PASSTHROUGH method with methodState PICK_UP_INIT. The PASSTHROUGH method sends the Identity response to the backend server (inside a RADIUS Access-Request packet). The backend server responds with some other request (passed PASSTHROUGH method inside a RADIUS Access-Challenge), and PASSTHROUGH method relays this request to the peer.

This continues until the backend server responds with Access-Accept or Accept-Reject. The PASSTHROUGH method notifies the Policy, stores the Success/Failure packet to succFailData, and sets methodState=END.

The policy then moves to SUCCESS or FAILURE state, and the Success/ Failure packet is sent to the peer.

6.4 Backend



The case where the conversation is started by the backend server (passthrough signals EAP-Start) does not require any special handling. The only difference to ordinary authenticator is that EAP retransmissions are handled by the NAS (AuthenticatorTimeout is set to INFINITY).

The case where the conversation is started by NAS requires special handling though. The client's response is passed to the backend in the first Access-Request.

The backend must process this request BEFORE it sends anything, for the following reasons:

- The identifier chosen for the next packet must be different from the one contained in client's response.
- The client's response will probably contain some useful information (e.g. Identity response).

If the passthrough wants the backend server to send the first EAP Request, it sets aaaEapStart=TRUE. Otherwise, when the passthrough receives an EAP Response from the peer, it stores it in aaaEapRespData, and sets aaaEapResp=TRUE.

These signals are sent to the backend using RADIUS or DIAMETER packets. In RADIUS, aaaEapStart signal corresponds to an Access-Request signifying EAP-Start (EAP-Message attribute with

no data), and aaaEapResp corresponds to an ordinary Access-Request (with aaaEapRespData stored in EAP-Message attribute). See [I-D.aboba-radius-rfc2869bis] for details.

When the backend has finished processing the signal, it sets one of the variables aaaAccept, aaaReject, aaaChallenge, aaaPacketDiscard, and unless aaaPacketDiscard is set, also aaaEapReqData. If aaaAccept is set, aaaEapKey can also be set.

These signals are returned to the passthrough using RADIUS or DIAMETER packets. In RADIUS, the first three signals correspond to Access-Accept, Access-Reject, and Access-Challenge packets, with aaaEapReqData stored in EAP-Message attribute. The fourth signal (aaaPacketDiscard) corresponds to Access-Challenge with Error-Cause set to 202. See [I-D.aboba-radius-rfc2869bis] for details.

If the passthrough does not receive a valid RADIUS response, even after retransmissions (handled by RADIUS), it sets aaaFailure. The passthrough can also set variable aaaIdentity, which contains the last Identity response seen. This can be used to route the RADIUS message to correct destination.

7 Security Considerations

This document's intent is to describe the EAP state machine fully. To this end, any security concerns with this document are likely a reflection of security concerns with EAP itself.

References

[IEEE.802-1X.2001]
Institute of Electrical and Electronics Engineers, "Local and Metropolitan Area Networks: Port-Based Network Access Control", IEEE Standard 802.1X, September 2001.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.

[RFC2284] Blunk, L. and J. Vollbrecht, "PPP Extensible Authentication Protocol (EAP)", RFC 2284, March 1998.

[I-D.ietf-eap-rfc2284bis]
Blunk, L., "Extensible Authentication Protocol (EAP)", draft-ietf-eap-rfc2284bis-01 (work in progress), February 2003.

[I-D.aboba-radius-rfc2869bis]
Aboba, B. and P. Calhoun, "RADIUS Support For Extensible Authentication Protocol (EAP)", draft-aboba-radius-rfc2869bis-19 (work in progress), April 2003.

Authors' Addresses

John R. Vollbrecht
Vollbrecht Consulting LLC
9682 Alice Hill Drive
Dexter, MI 48130
Phone: 734 426-1026
EMail: jrv@umich.edu

Pasi Eronen
Nokia Research Center
P.O. Box 407
FIN-00045 Nokia Group,
Finland
EMail: pasi.eronen@nokia.com

Nick L. Petroni, Jr.
Department of Computer Science
University of Maryland
A.V. Williams Building
College Park, MD 20742
Email: npetroni@cs.umd.edu

Yoshihiro Ohba
Toshiba America Information Systems, Inc.
9740 Irvine Blvd.
Irvine, CA 92619-1697
USA
EMail: yohba@tari.toshiba.com

Appendix A. Open Issues

The following are issues and questions to be resolved with the EAP working group. These include issues to be clarified as well as issues about interface with other layers.

A.1 Authenticator

- 2869bis: "The NAS MUST NOT "manufacture" a Success or Failure packet as the result of a timeout. After a suitable number of timeouts have elapsed, the NAS SHOULD instead end the EAP conversation." Issue: There is a RADIUS client issue - how many retries before giving

up. There is also the issue that continues to come up of what to do with Access Accept with EAP Failure. As it stands this will cause the authenticator to go to fail and send a Success to the Peer. Probably this is right, but one more review of this seems reasonable.

- 2869bis: "Also, the RADIUS server is advised to permit only a modest number of invalid EAP packets within a single session, prior to terminating the session with an Access-Reject. By default a value of 5 invalid EAP packets is recommended." Issue: RADIUS server does not control retransmissions. It will respond to every Request, with an Access Accept/Fail/Challenge or Packet Challenge. The Packet Challenge is sent when the EAP message fails integrity check. Given this, how should the sentence in 2869 be interpreted?
- Methods (including pass-through) should be able to modify the retransmission timeout. In some cases, the timer should use exponential back-off or something. Issue: what does this mean for the state machine, if anything?
- Do we need a new variable to signal the lower layer that keying material is available (in eapKey), or is it enough that the lower layer checks if eapKey!=NONE after getting eapSuccess?

A.2 Peer

- 2284bis: "If a peer receives a duplicate Request before it has sent a Response, but after it has determined the initial Request to be valid (i.e. it is waiting for user input), it MUST silently discard the duplicate Request. " Issue: Seems like the peer should be able to send as many responses as it gets requests for the same id. It may not send a response for prior id after it has sent a response to current id. This is how the state machine works, and hopefully the wording in 2284bis will be modified to match.
- What to do if we get a timeout, Policy.isSatisfied() is TRUE, but methodState is not CON_ACC? Issue: can peer go into authenticated state without getting a Success -either internal to the method (Con_ACC) or and EAP Success?
- What to do if we get an altAccept, Policy.isSatisfied() is TRUE, but methodState is not CON_ACC? Issue: same as above
- Do we need a new variable to signal the lower layer that keying material is available (in eapKey), or is it enough that the lower layer checks if eapKey!=NONE after getting eapSuccess?

Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on the IETF's procedures with respect to rights in standards-track and standards-related documentation can be found in BCP-11. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementors or users of this specification can be obtained from the IETF Secretariat.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights which may cover technology that may be required to practice this standard. Please address the information to the IETF Executive Director.

Full Copyright Statement

Copyright (C) The Internet Society (2003). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English. The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns. This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE."

Expiration Date

This memo is filed as <draft-vollbrecth-eap-state-02.ps>, and expires October 22, 2003.